



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

KbdGetHWID

Returns the type of keyboard in use. The hardware ID specifies the type of keyboard attached and is defined by the manufacturer.

Syntax

```
KbdGetHWID(pkbdhwid, hkbd)
```

Parameters

- pkbdhwid (PKBDHWID) - output : A pointer to a [KBDHWID](#) structure in which the keyboard hardware ID is returned.
- hkbd (HKBD) - input : Reserved. Must be 0.

Return Code

return (APIRET) - returns

KbdGetHWID returns one of the following values:

- 0 NO_ERROR
- 373 ERROR_KBD_PARAMETER
- 439 ERROR_KBD_INVALID_HANDLE
- 447 ERROR_KBD_KEYBOARD_BUSY
- 504 ERROR_KBD_EXTENDED_SG

Remarks

The hardware ID indicates the basic layout of the keyboard, such as whether or not a numeric keypad exists. It gives no information about key values.

From:
<https://cocorico.osfree.org/doku/> - **osFree wiki**

Permanent link:
<https://cocorico.osfree.org/doku/doku.php?id=en:docs:fapi:kbdgethwid&rev=1636020807>

Last update: **2021/11/04 10:13**

