

VioEndPopup

Bindings: C, MASM

This call is issued by the application when it no longer requires the temporary screen obtained through a previous [VioPopUp](#) call.

VioEndPopUp (VioHandle)

VioHandle (**HVIO**) - input A reserved word of 0s.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
405	ERROR_VIO_NO_POPUP
436	ERROR_VIO_INVALID_HANDLE

Remarks

When the application issues a [VioEndPopUp](#) call, all video calls are directed to the application's normal video buffer.

PM Considerations

An error is returned if issued with a non-zero handle.

C bindings

```
#define INCL_VIO

USHORT rc = VioEndPopUp(VioHandle);

HVIO          VioHandle;    /* Vio device handle */

USHORT        rc;          /* return code */
```

MASM bindings

```
EXTRN VioEndPopUp:FAR
INCL_VIO EQU 1

PUSH WORD VioHandle ;Vio device handle
CALL VioEndPopUp

Returns WORD
```

From:

<https://cocorico.osfree.org/doku/> - **osFree wiki**

Permanent link:

<https://cocorico.osfree.org/doku/doku.php?id=en:ibm:prcp:vio:endpopup>

Last update: **2016/09/14 10:49**

